



## Non-Intrusive Ultrasonic Clamp-on Flow Measurement of Liquids and Gases

# FLUXUS® F/G80X For Operation in Hazardous Areas

Chemical Industries

Petrochemical Industries

Downstream - Refining

Midstream -  
Hydrocarbon Transport

E&P - Offshore / Onshore

FM-C Class I, Div. 1/2  
ATEX, IECEx Zone 1



FLEXIM Sets Standards  
*when measuring matters*



# FLUXUS® F/G80X

## Specifically Designed for Demanding Environments

---

### From Oil & Gas Exploration and Production to Petrochemical and Chemical Processing

From wellhead to refinery, the flows of crude oil, natural gas and refined products need to be measured every step of the way. Harsh environments with corrosive atmospheres offshore or hot and dirty applications during crude oil refining require tough solutions.

Also during chemical processing, liquid media such as acids, caustics as well as highly viscous organic substances or highly pressurized gas lines place enormous material and mechanical stress upon wetted flow measurement technologies.

#### FLEXIM offers the better alternative:

- Being non-intrusive, the measurement system never comes into contact with the media inside the pipe and therefore does not suffer any wear and tear.
- Ultrasonic transducers are simply clamped onto the outside of the pipe - plant shut-downs for installation are a thing of the past.
- The measurement system can never be the cause of a pipe leak, cannot be prone to clogging and is virtually maintenance-free.
- It is suitable for all pipe sizes from 3/8 inch in diameter and up, with no limitation on pipe material, wall thickness and media temperature.
- FLEXIM's ultrasonic flowmeters offer exceptional reliability and accuracy even at high and low flows due to their matched, calibrated and temperature compensated transducer pairs as well as sophisticated internal signal processing.
- With measurement from outside of the pipe wall, the system offers a long lifetime as well as high energy efficiency as pressure losses inside the pipe are avoided.

FLEXIM's permanently installed and portable flowmeters for explosive and hazardous areas have already been proven worldwide in many demanding applications with major operators.

#### Chemical Industry

---

- Hazardous Organic and Inorganic Media
- Acids and Caustics
- Process Gases
- Polymerization Processes
- Infrastructural Processes

#### Hydrocarbon Products Handling

---

- Hydrocarbon Products Flow Measurement
- Pipeline Integrity Monitoring
- Allocation Terminals
- LNG Terminals
- Underground Gas Storage
- Gas Distribution and Compressor Stations

#### Crude Oil Refining and Gas Processing


---

- Distillation Columns
- Cracker and Coker Units
- Petrochemical Processes
- Gas Processing

#### Oil & Gas Exploration On- & Offshore

---

- FWKO and Separator Outlets
- Coalescers
- Scrubbers and Reboilers
- Produced Water Management
- Chemical Injection



## Advantages

- Bi-directional flow measurement of liquids and gases in FM-C Class I, Div. 1/2 and ATEX / IECEx Zone 1 areas
- Very cost effective:
  - No pipe works
  - No process shut-downs
  - Virtually maintenance-free
- Matched, paired and wet calibrated flow transducers (traceable certification to national standards)
- Excellent zero point stability and drift-free
- Wide turndown ratio
- Independent of pipe size, material, operating pressure, medium and temperature
- High tolerance to entrained solids and gases
- Free of wear, tear and abrasion
- Not prone to clogging or corrosion
- No pressure loss or source of potential leaks and fugitive emissions

## Rugged, Reliable, Versatile

With its flameproof housing and stainless steel (SS316, NEAM 6X / IP68 optional) corrosion resistant transducers residing inside the PERMAFIX or PERMALOK mounting fixture, ensuring permanent contact pressure and high mechanical stability, the FLUXUS® F/G80X series is perfectly suited for every demanding industrial application.

The connection and electronic compartment of the FLUXUS® F/G80X series are hermetically sealed, so that the measurement system provides maximum operational reliability and safety, being FM Class I, Div. 1/2 and ATEX / IECEx Zone 1 approved.

Not only is the FLUXUS® F/G80X rugged and reliable, it is precise. Thanks to carefully matched and temperature compensated transducers (fully ANSI / ASME MFC 5M compliant) the FLUXUS® F/G80X offers an unmatched zero point stability and precise bi-directional flow measurement over a virtually unlimited turndown range.

The F808 single channel liquid flow meter is also available with an extra low flow option, allowing reliable and repeatable measurements, typically between 1 and 5 gal/h on line sizes from ¼ to 1½ inches.



# FLUXUS® F/G80X

FM-C Class I, Div. 1/2 and  
ATEX / IECEx Zone 1 approved  
liquid and gas flow meter



## Technical Facts

<b>FLUXUS® F808</b>	Single channel, non-intrusive ultrasonic flowmeter for liquids in hazardous areas
<b>FLUXUS® F809</b>	Dual channel, non-intrusive ultrasonic flowmeter for liquids in hazardous areas
<b>FLUXUS® G809</b>	Dual channel, non-intrusive ultrasonic flowmeter for gases in hazardous areas
<b>Hazardous area approvals:</b>	FM-C Class I, Div.1/2 for F808 FM-C Class I, Div. 1 for F/G809
<b>Operating temperature - transmitter:</b>	-22 °F to +140 °F
<b>Physical quantities:</b>	volumetric flow rate, mass flow rate, flow velocity
<b>Degree of protection Transmitter:</b>	NEMA 4X / IP66)
<b>Flow velocity range</b>	
<b>Liquids:</b>	0.03 to 82 ft/s
<b>Gases:</b>	0.03 to 115 ft/s
<b>Pipe temperatures</b>	
<b>Liquids:</b>	-40 °F to +390 °F [-310 °F to +1100 °F by employing the patented Wavelnjector® mounting fixture]
<b>Gases:</b>	-40 °F to +210 °F
<b>Pipe diameter range</b>	
<b>Liquids:</b>	0.4 inch up to 255 inches
<b>Gases:</b>	1.5 inches to 82 inches (up to 1.4 inch wall thickness)
<b>Repeatability:</b>	0.15% of reading ± 0.03 ft/s
<b>Calibrated accuracy*</b>	
<b>Liquids:</b>	± 0.5% of reading ± 0.03 ft/s, field calibration** ± 1% of reading ± 0.01 ft/s, NIST traceable
<b>Gases:</b>	± 0.5% of reading ± 0.03 fts, field calibration** ± 1% to 3% of reading ± 0.03 ft/s, NIST traceable
<b>Data logger capacity:</b>	>100 000 measured values
<b>Loggable values:</b>	all physical quantities, totalized values and diagnostic values
<b>Outputs:</b>	2 for F808, 4 for F/G809 (various combinations of current, binary, Modbus and HART outputs are available)
<b>Communication interface:</b>	Modbus RTU, HART
<b>Power supply:</b>	100 to 240 V AC / 50 to 60 Hz or 20 to 32 V DC

\* under reference conditions and with  $v > 0.45$  ft/s

\*\* if reference uncertainty better than  $< 0.2\%$

Further information can be found in the according F/G80X Technical Specifications at [www.flexim.com](http://www.flexim.com)

**FLEXIM AMERICAS  
Corporation  
Headquarter  
250-V Executive Drive  
Edgewood, NY 11717  
Phone: (631) 492-2300**

FLEXIM has offices located throughout North America. Please have a look for your local representative at:

**[www.flexim.com](http://www.flexim.com)**

**or call us at:**

**1-888-852-PIPE**

